



### **PHYSICAL DATA**

- Weight of bare panel - 42 lb.
- Height of bare panel - 1.38"
- Fire rating of bare panel:  
Class A Flame Spread  
Non-Combustible Materials

### **PERFORMANCE DATA**

- Concentrated Load rating - 2,000 lbf (6672 N)
- Uniform Load rating - 600 psf (2669 kg/M<sup>2</sup>)
- Ultimate Load rating - 6,300 lbf (28023 N)  
Safety Factor - 3-to-1 Min.
- Impact Load rating - 200 lb. (91 Kg)
- Rolling Load Rating:  
CISCA Wheel A (10 Pass) - 1,500 lbf (6672 N)  
CISCA Wheel B (10K Pass) - 1,250 lbf (5560 N)

### **FINISH OPTIONS**

- HPL tile (1/8" or 1/8")  
ASM "Smart-Trim", "Dura-Trim" or "Mono"
- Vinyl tile:  
VPT "Con-Tile" (static conductive)  
VPT "Stat-Tile" (static dissipative)
- Rubber tile:  
Antistatic  
Standard
- Bare surface
- Bare corner-lock  
Contact ASM for other tile options, such as bamboo, cork, ceramic, wood, stone, etc.

### **UNDERSTRUCTURE OPTIONS**

- Free standing - stringerless
- Corner-Lock
- Rigid Grid bolted stringers:  
2' x 2' system  
2' x 4' system  
4' x 4' Basketweave system

### **FEATURES**

- Available in 24" or 600mm size
- Powder coat epoxy paint finish
- Welded steel construction
- Full-hard steel top sheet
- Full-strength, deep drawn corners
- Light weight cementitious fill with fiberglass
- Recycled material content = 43.7%

**NOTE:** Data sheet drawing and information are subject to change without prior notice.

**ASM Modular System Inc. °**

9500 Industrial Center Dr. Ladson, SC, 29456 Tel: 843-534-1110 Fax: 843-534-1111 ([www.asmproducts.com](http://www.asmproducts.com))

CS - 8516