



PHYSICAL DATA

- Weight of bare panel - 51 lb.
- Height of bare panel - 1.43"
- Fire rating of bare panel:
Class A Flame Spread
Non-Combustible Materials

PERFORMANCE DATA

- Concentrated Load rating - 3,000 lbf (13344 N)
- Uniform Load rating - 1,000 psf (4482 kg/M²)
- Ultimate Load rating - 10,000 lbf (44480 N)
Safety Factor - 3-to-1 Min.
- Impact Load rating - 400 lb. (181 Kg)
- Rolling Load Rating:
CISCA Wheel B (10 Pass) - 3,000 lbf (13344 N)
CISCA Wheel C (10K Pass) - 3,000 lbf (13344 N)

FINISH OPTIONS

- HPL tile (1/16" or 1/8")
ASM "Smart-Trim", "Dura-Trim" or "Mono"
- Vinyl tile:
VPT "Con-Tile" (static conductive)
VPT "Stat-Tile" (static dissipative)
- Rubber tile:
Antistatic
Standard
- Bare surface
- Bare corner-lock
Contact ASM for other tile options, such as bamboo, cork, ceramic, wood, stone, etc.

UNDERSTRUCTURE OPTIONS

- Free standing - stringerless
- Corner-Lock
- Rigid Grid bolted stringers:
2' x 2' system
2' x 4' system
4' x 4' Basketweave system

FEATURES

- Available in 24" or 600mm size
- Powder coat epoxy paint finish
- Welded steel construction
- Full-hard steel top sheet
- Full-strength, deep drawn corners
- Light weight cementitious fill with fiberglass
- Recycled material content = 45.9%

NOTE: Data sheet drawing and information are subject to change without prior notice.