



PHYSICAL DATA

- Weight of bare panel - 26 lb.
- Height of bare panel - 1.38"
- Fire rating of bare panel:
Class A Flame Spread
Non-Combustible Materials

PERFORMANCE DATA

- Concentrated Load rating - 1,500 lbf (6672 N)
- Uniform Load rating -
@ 0.040" deflection - 450 psf (2196 kg/M²)
@ 0.060" deflection - 750 psf (3660 kg/M²)
- Ultimate Load rating - 5,000 lbf (22,240 N)
Safety Factor - 3-to-1 Min.
- Impact Load rating - 150 lb. (68 Kg)
- Rolling Load Rating:
CISCA Wheel A (10 Pass) - 600 lbf (2669 N)
CISCA Wheel B (10K Pass) - 600 lbf (2669 N)

FINISH OPTIONS

- HPL tile (1/16" or 1/8")
ASM "Smart-Trim", "Dura-Trim" or "Mono"
- Vinyl tile:
VPT "Con-Tile" (static conductive)
VPT "Stat-Tile" (static dissipative)
- Rubber tile:
Antistatic
Standard
- Bare surface
- Bare corner-lock
Contact ASM for other tile options, such as bamboo, cork, ceramic, wood, stone, etc.

UNDERSTRUCTURE OPTIONS

- Free standing - stringerless
- Corner-Lock
- Rigid Grid bolted stringers:
2' x 2' system
2' x 4' system
4' x 4' Basketweave system

FEATURES

- Available in 24" or 600mm size
- Powder coat epoxy paint finish
- Welded steel construction
- Full-hard steel top sheet
- Full-strength, deep drawn corners
- Recycled material content = 36.6%