



### PHYSICAL DATA

- Weight of bare panel - 13.6 Kg (30 lb.)
- Height of bare panel - 34mm (1 5/16")
- Fire rating of bare panel:  
Class A Flame Spread  
Non-Combustible Materials

### PERFORMANCE DATA

- Concentrated Load rating - 3,550 N (800 lbf)
- Uniform Load rating - 9,600 N/M<sup>2</sup> (200 psf)
- Ultimate Load rating - 14,520 N (3,200 lbf)  
Safety Factor - 3-to-1 Min.
- Impact Load rating - 670 N (150 lbf)
- Rolling Load Rating:  
CISCA Wheel A (10 Pass) - 3,560 N (800 lb.)  
CISCA Wheel B (10K Pass) - 2,670 N (600 lb.)

### FINISH OPTIONS

- HPL tile - 1.5 or 3.0 (1/16" or 1/8")  
ASM "Smart-Trim", "Dura-Trim" or "Mono"
- Vinyl tile:  
VPT "Con-Tile" (static conductive)  
VPT "Stat-Tile" (static dissipative)
- Rubber tile:  
Antistatic  
Standard
- Bare surface
- Bare corner-lock  
Contact ASM for other tile options, such as bamboo, cork, ceramic, wood, stone, etc.

### UNDERSTRUCTURE OPTIONS

- Free standing - stringerless
- Corner-Lock
- Rigid Grid bolted stringers:  
60cm x 60cm (2 ft. x 2 ft.) system  
60cm x 120cm (2 ft. x 4 ft.) system  
120cm x 120cm (4 ft. x 4 ft.)  
Basketweave system

### FEATURES

- Available in 600mm or 24" size
- Powder coat epoxy paint finish
- Welded steel construction
- Full-hard steel top sheet
- Full-strength, deep drawn corners
- Light weight cementitious fill with fiberglass
- Recycled material content = 45.5%